MATERIAL SAFETY DATA SHEET

INDENTIFICATION:
Product Name: DYNACLEAR® CBT
Chemical Name: Bi-axially Oriented Polyolefin Copolymer Blown Film

INGREDIENTS:

MATERIAL SAFETY DATA SHEET
This product contains linear low-density polyethylene and polypropylene
Hazardous components: Not applicable.

PHYSICAL DATA:
Form: Thin solid film or sheet
Odor: None
Appearance: Transparent film
Solubility: Insoluble in water
Density: 0.92 g/cc
Boiling Point: Not applicable
Vapor Pressure: Not applicable

HAZARDOUS COMPONENTS:
Material: None
Additives: None
Presence of chemicals classified as carcinogenic or otherwise hazardous: None

FIRE AND EXPLOSION HAZARDS:
No unusual hazard
Extinguishing materials: water, CO2, foam
Fumes: HCL fumes if exposed to fumes, use mask or breathing apparatus

HEALTH HAZARDS:
Eye: Solid or dust may cause irritation or corneal injury due to mechanical action.
Ingestion: Very low toxicity
Skin Contact: Non-irritant
Inhalation: Fumes produced during hot wire sealing are of low toxicity and are not harsh, however, local ventilation is advised.
Effects of Chronic Exposure: None
First Aid: If ingested, no known health effect. Skin contact with molten plastic should be treated with cold water before it is removed, then wrap in clean gauze and seek medical attention.

PROTECTION INFORMATION ADVISE:
Control measure: None
Eyes: No protection needed, regulation safety glasses should be used as good practice.
Skin: No gloves required.
Lungs: Local ventilation to prevent fume buildup in sealing areas is advised for comfort.

REACTIVITY:
Stability: Stable
Reactive Polymerization: Does not occur
Incompatibility: None

STORAGE CONDITIONS:
Cool and Dry storage.
Recommended storage temperatures: Do not store above 130o F.
Do not expose to direct sunlight.

TRANSPORTATION INFORMATION:
Not regulated

Offices, Warehouse & Service: 500 West Main Street, Unit 12 - Wyckoff, NJ 07481
Ph. 201.337.1001 - **Fax** 201.337.5001

www.shrinkfilm.com - info@shrinkfilm.com